

Commercial Vinyl Ambient


Specifications:




Slip
resistant




Thermal
resistance



Dimensional
stability



Light
fastness



Stocked in
New Zealand



15
year guarantee

Level of use ISO 10874 -	23 - 33 - 42
Total thickness -	2.50 mm
Wear layer -	0.70 mm
Wear layer PUR treatment -	PU Laquer
Total weight -	2600 g/m ²
Width -	2 m
Standard length -	25 m
Inflammability EN 13501-1 -	Bfl-S1
Critical Radiant Flux ISO 9239-1 -	8.1kW/m ²
Slip resistance DIN 51130 -	DS
Slip restraint -	R10
Residual indentation EN ISO 24343-1 -	≤ 0.10 mm
Dimensional stability EN ISO 23999-	≤ 0.40 %
Light fastness EN ISO 105 B02-	≥ 6 degrees
Underfloor heating -	Suitable
Warranty -	5 years commercial 15 years residential

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

