Queenstown[™] 1.2

Technical Data

Product Classification

Type of floor covering		Laminate flooring
Warranty*	Residential	15 years

*All warranties are in addition to any rights consumers may have under Australian and New Zealand consumer laws. Terms and conditions apply - for full information in respect to the scope of the residential warranty, please see armstrongflooring.au or armstrongflooring.co.nz or contact our Head Office.

Physical Properties

Colours (Standard)	12
Overall thickness (mm)	8.0
Wear rating	AC3
Bevel	Micro
Core type	HDF (860kg/m ³)
Locking system	Angle/Angle - Side Tap (Manufactured under license from Unilin BV)
Backing type	Balancing layer
Dimensions (mm)	1215 x 195
Planks/carton	8
m²/carton	1.90
m²/pallet	133
kg/carton	14.0

Installation

To current Armstrong Flooring Laminate Flooring Installation Instructions

Sustainability TVOC Emissions Compliant with Green Building Council low emitti

VOC emission rates
 100 611153101114165

Technical Performance

Slip Resistance	AS 4586 Wet Pendulum (Appendix A)	P3	
Fire Resistance (Floor)	AS ISO 9239-1 Critical Radiant Flux (CHF Value) Smoke Development Rate	≥ 4.5kW/m² ≤ 750%.min	
Other	ISO 24336 Thickness swelling ISO 4760	< 10%	
	Surface swell and recovery swell	No change	

Accreditation

Manufactured under accredited ISO 9001 quality and ISO 14001 environmental management systems

All specifications are current as at date of publication and may be changed without notice. For current and complete specifications please visit armstrongflooring au or armstrongflooring. All Armstrong Flooring products must be installed in accordance with the relevant Australian and/or New Zealand applicable standards and the Armstrong Flooring Installation Instructions. Variations may occur between samples, photographic images, and batches in terms of colour, shade, pattern or similar.

AU: www.armstrongflooring.au/queenstown1.2 NZ: www.armstrongflooring.co.nz/queenstown1.2

